

## Fishfinder 160C



### Physical & Performance:

Unit dimensions, WxHxD:	6.1" x 4.9" x 2.9" (15.5 x 12.4 x 7.4 cm)
Display size, WxH:	3.2" x 3.2" (8.0 x 8.0 cm)
Display resolution, WxH:	128 x 128 pixels
Display type:	16-color CSTN
Weight:	17.6 oz (499 g)
Waterproof:	yes (IPX7)

### Features:

CANet® compatible:	no
Audible alarms:	yes
Dual-frequency sonar capable:	no
Dual-beam sonar capable :	yes
Split-screen zoom:	no
Ultrascroll™ (displays fish targets at higher boat speeds):	yes
See-thru® technology (exposes fish hidden in cover):	yes
Fish Symbol ID (helps identify fish targets):	yes
AutoGain Technology (minimizes clutter, maximizes targets):	yes
Whiteline (indicates hard or soft bottom):	yes
Adjustable depth line (measures depth of underwater objects):	no
A-scope (real time display of fish passing through transducer beam):	no
Bottom lock (shows return from the bottom up):	no
Water temperature log and graph:	yes
Water temperature sensor included:	no
Water speed capable (displays speed on water):	yes

### Other:

Frequency:	80/200 kHz (dual beam)
Transmit power:	150 W (RMS), 1200 W (peak to peak)
Voltage range:	10-18 VDC
Maximum depth:	900 ft
Cone angle:	45° or 15° (dual beam)